

APPLICANT: TELEFONAKTIEBOLAGET L M ERICSSON (publ)

TITLE: METHOD AND APPARATUS FOR
EXECUTING SECURE DATA TRANSFER IN
A WIRELESS NETWORK

ins A' B
g Background
~~Field of the Invention~~

5
10 The present invention relates to a method and appar-
atus for secure data transfer between a communication de-
vice and an application server in a wireless network, and
more particularly to a method for secure data transfer
between a communication device, provided with a SIM card,
and an application server in a wireless network using WAP
15 (Wireless Application Protocol) for the data transfer,
wherein said SIM card contains a secret/private key, an
algorithm for signing of data, a SAT application for
handling the signing dialogue and the signing of data.

20 ~~Description of the Prior Art~~

Several protocols for data transfer over wireless
networks have been proposed by different mobile phone manu-
factures. Ericsson, Motorola, Nokia Mobile Phones, and
Uniwired Planet have developed a joint standard called
25 Wireless Application Protocol (WAP). The purpose of the
Wireless Application Protocol is to provide operators,
infrastructure and terminal manufactures, and content
developers a common environment enabling development of
advanced services for digital mobile phones and other wire-
less terminals or portable communication devices. For
30 example, the WAP enables e-mail and Internet access from a
digital mobile phone.

Certain services and WAP applications provided via
Internet, such as ordering, order confirmations, bank
35 services, etc, and associated transactions require a high
level of security.

05676105-052300

WO 99/01848 discloses a procedure, which is applicable for the control of keys to applications making use of the subscriber identity module (SIM) in a mobile phone and for the control of license agreements concerning the use of such applications. Further, the procedure provides data security that allows safeguarding of the interests of the operator, module manufacturer, application developers and users of applications. A key list comprising one or more application-specific keys is stored in the subscriber identity module. A corresponding list is also stored in an application control server connected to the network, which takes care of the control of applications stored in subscriber identity modules. The application stored in the subscriber identity module is activated and/or closed by using the key list.

DE-A1-198 16 575 describes a method for running special applications, such as a virtual charge card, entirely or partly, in a SIM. Further, it is suggested using the SIM toolkit as a means for communication. Security is provided by means of the conventional security means and procedure of the SIM-card. For example, an anti theft security for the special application authorisation and the service data in combination with one or more PIN-codes of the SIM-card.

WO 98/37663 discloses a method for checking authorisation incorporating a way to impart to a smart card an encryption key and including a way to cause a microprocessor, by means of the encryption key and at least one number, to perform a calculation whose result comprises a first signature. The signature together with said number are transferred to a system for which authorisation is to be shown which includes a computer in which said encryption key is stored. The computer is programmed to carry out the calculation to obtain the signature and then to compare the latter signature with the first signature for the verification.

In the above mentioned methods all information transfer is done through SAT (SIM Application Toolkit) applications, in which the security solution also is implemented.

Another way of solving the security problem is to
5 provide one-time password pads, wherein a "new" password is entered via the key pad of the mobile phone or the communication device every time an application is used.

There are several problems and disadvantages associated with the above mentioned prior art solutions. The
10 security level is too low for higher values: passwords could be discovered and the password has to be entered manually making WAP applications very user unfriendly compared to for example pure SAT applications and, of course, the password has to be remembered.

15

Summary of the Invention

It is an object of the present invention to provide an improved method and system for executing secure data transfer between a communication device, provided with a
20 smart card, such as a SIM card, and an application server in a wireless network using a data transfer protocol such as WAP (Wireless Application Protocol) for the data transfer.

This is accomplished by a method and system according
25 to the invention for executing secure data transfer on the application level for communication applications executing on mobile phones according to the invention. The smart card contains a secret/private key, an algorithm for signing of data, a signing application for handling the signing
30 dialogue and the signing of data. A communication application, such as a WAP application, is installed on the communication device enabling communication with the application server by means of a dialogue, and information browsing on the server is initiated from the communication device,
35 wherein data are transferred between the server and the

communication device. Further, a request requiring a secure transaction of data is send from the communication device to the server, and an agreement proposal for the secure transaction is send from the server to the communi-cation device. If the agreement proposal is considered acceptable, the agreement proposal is returned to a security adapter. The WAP application in the communication device is suspended or terminated. Details of the transaction to be secured and a sign request are entered into at least a message, such as SMS or USSD packets, from the adapter to the smart card in the communication device in order to activate the signing application. The details of the transaction and a prompt for an accept are displayed on the communication device. If the transaction is accepted, the signing application signs the data to be send with the secret/ private key by using the algorithm, the signed data are send from the communication device to the security adapter via messages. The signature is verified and the verified signed data are send to the server for the final execution of the transaction.

Another object of the invention is to provide an apparatus for connection to a wireless network for monitoring the data transfer between the communication device and the application server.

This is accomplished by a security adapter according to the invention, providing a high level of security in data transfer on the application level for communication applications executing on communication devices.

An advantage of the present invention is that a high level of security in the data transfer is achieved in combination with conventional WAP browsing. An additional advantage is that the application on the SIM card can be made very thin and flexible, because it only has to handle signing of data and no information or menu handling.

Further, the system handling the information browsing and

the system handling the security of the transactions are separated and, therefore, they can be updated and changed independently.

5 **Brief Description of the Drawings**

Other objects, advantages and features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings, in which

10 FIG 1 illustrates a first embodiment of a network configuration comprising a security adapter according to the invention,

FIG 2 illustrates a second embodiment of a network configuration comprising a security adapter according to
15 the invention,

FIG 3 is a flowchart of a first embodiment of the method according to the invention, and

FIG 4 is a flowchart of a second embodiment of the method according to the invention.

20

Detailed Description of the Invention

With reference to FIG 1 of the drawing, there is shown a first embodiment of a network configuration for executing secure data transfer between a communication
25 device, such as a mobile phone, and an application server in a wireless network using WAP (Wireless Application Protocol) for the data transfer. The network configuration comprises a WAP (Wireless Application Protocol) mobile phone 1 - provided with a subscriber identity module (SIM)
30 - for communication with a GSM (Global System for Mobile communications) mobile communication network 2. Additionally, the SIM card contains a secret/private key, an algorithm for signing of data to be transferred, and a SAT (SIM Application Toolkit) application for handling the signing
35 dialogue and the signing of data. The GSM network 2 is

connected to the Internet 3 via a WAP-gateway 4. Further, an application server 5 providing WAP applications is also connected to the Internet 3. Additionally, a security adapter 6 according to the invention is connected to the WAP-gateway for monitoring the communication between the mobile phone 1 and the application server 5.

A second embodiment of a network configuration comprising a security adapter 6 according to the invention is shown in FIG 2. In this embodiment of the network configuration the security adapter 6 is connected to the application server 5.

FIG 3 is a flowchart of a first embodiment of the method according to the invention for executing secure data transfer between a mobile phone and an application server in a wireless network.

In a first step 301, a WAP application, such as a microbrowse, is installed on the mobile phone 1 enabling communication with the application server 5 by means of a WAP dialogue.

A conventional information browsing session on the server is initiated either by a user (subscriber) from the mobile phone 1 or the application server 5 in step 302, wherein data are transferred to/from the mobile phone 1, over the GSM network 2 interfacing the Internet via the WAP gateway, from/to the application server 5. For example, a user browses to a web site providing information accessible via a WAP dialogue from the mobile WAP phone 1. The site belongs to a bookstore offering a service wherein books can be bought directly from the site. A book is selected by the user from a list of books presented on the site. When the user decides to buy the book he selects "order" from an order menu of the site. This action initiates a sequence of operations.

First a request requiring a secure transaction of data is send from the mobile phone to the application

server 5 or from the application server to the mobile phone 1 in step 303. An agreement proposal for the secure transaction is send from the server 5 to the mobile phone in step 304. If the agreement proposal is considered acceptable by the user in step 305, the agreement proposal is send to the security adapter 6 in step 306, and the WAP application in the communication device is suspended or terminated in step 307.

Details of the transaction to be secured and a sign request are entered into at least one SMS or USSD packet by the security adapter 6 in step 308. The SMS packet(s) is send from the security adapter 6 to the SIM card in the mobile phone in order to activate the SAT application in step 309. The details of the transaction and a prompt for an accept from the user are displayed on the communication device in step 310. If the transaction is accepted in step 311, the SAT application signs the data to be send with the secret/private key by using the algorithm in step 312.

The signed data is send from the communication device 1 to the security adapter 6 via SMS or USSD packets in step 313. The security adapter 6 forwards the signature for verification in an entity, such as a backend system, operatively connected to the server 5 in step 314, and the verified signed data is send to the server for the final execution of the transaction in step 315.

A flowchart of a second embodiment of the method according to the invention is shown in FIG 4. A WAP application is installed on the mobile phone 1 enabling communication with the application server 5 by means of a WAP dialogue in step 401.

Information browsing on the server 5 is initiated from either the application server 5 or the mobile phone 1, wherein data are transferred over the network between the application server 5 and the mobile phone 1 in step 402.

S

10

25

30

35

5 In another embodiment of the invention a more generic
solution for handling the dialogue with the user is imple-
mented. A command interpreter implemented on the SIM card
is used, allowing more dynamic downloading/updating of com-
mands defining the application that communicates with the
10 user.

In still another embodiment of the invention the mobile phone have means whereby the user can be assured that he is really communicating directly with the security application and not with an application impersonating the real application. This is implemented as a particular icon, character, font, colour etc only available to certain applications or the operating system in the phone.

In one embodiment of the security adapter 6, it is an electronic apparatus with digital computer capabilities and an internal memory for storage of a computer program product or element. The computer program product comprises software code portions for performing the operation and functions of the security adapter 6, i.e. receive an agreement proposal for a secure transaction from the communication device 1, create and send a message to the communication device in order to activate the signing application, receive signed data send from the communication device 1, and send the signed data for verification and then further to the application server 5 for execution of the transac-

tion. In an alternative embodiment, the computer program element is embodied on a computer readable medium.

05676186 052900